


OFFICE OF THE MARION COUNTY SURVEYOR
SECTION RECORD CORNER
SECTION 28 TOWNSHIP 17 RANGE 5
DATE: -1-14-2000- 5-17-05
PARTY CHIEF: -Kiste- Wilcoxon
CREW: _____
TYPE OF MARKER: Harrison
METHOD OF ESTABLISHMENT: County: 6-26-95

IN. S.P.C. E ZONE, NAD 83
NAME: 17052801
N: 516265.7685(m)
E: 73534.3366(m)



Original post set 1821 by Laughlin with witnesses: 6" beech N 5 E 3 links, 6" beech N 30 W 13 links. Legal 8-1854 by Wilson per Lawrence Township Legal Survey Book pg. 10 called the corner "0" stone. Legal 10-1860 by Smith also Legal 10-1874 by Voorhis both per Lawrence Township Legal Survey Book pg. 13 called distances. Legal 3-1854 by Wilson per Lawrence Township Legal Survey Book pg. 14 called corner "L" stone. One witness stone called distance to S per Lawrence Township Legal Survey Book pg. 35 called corner "M" 'found rock'. 6-10-47 Walton called 'large brown stone 6" down'. Cut cross per Walton, 2-11-70 SeFranka called a railroad spike. Cripe 10-2-73 called found no cut cross. Railroad spike re-set over stone. 5-2-75 Fortner called the same. Redrawn in 1975. Excavated 7-1-82 by Cleveland. Railroad spike found at surface over stone. Stone removed and Harrison set. Re-tied 6-26-95 by Wilcoxon. Re-tied 1-14-2000 by Kiste.

HC752801

REF.	DISTANCE	DESCRIPTION
1.	65.89'	Cut 'x' S-bolt of signal base
2.	122.59'	Boat spike S PwP#40-251DA 12"up
3.	72.94'	Cut 'x' N-bolt of signal base
4.	60.18'	Cut 'x' NW-bolt of signal base
5.		Center of bee hive inlet
6.	45.53'	PK nail E PwP#23-251DA 12"up
7.	48.84'	Cut 'x' NE-bolt of signal base
8.	108.73'	PK nail E PwP#42-251DA 8"up